

APEX® 3174

Teknor Apex Company - Flexible Polyvinyl Chloride

Friday, June 30, 2017

General Information						
Product Description						
Applications include weather-str	rip, spline, profiles, "T" moldings.					
General						
Material Status	Commercial: Active					
Availability	 Africa & Middle East Asia Pacific	EuropeLatin America	North America			
Features	 General Purpose 					
Uses	 Hose Profiles	 Tubing Weatherstripping				
Appearance	Natural Color	Opaque				
Forms	• Pellets					
Processing Method	 Extrusion 					

ASTM & ISO Properties 1					
Physical	Nominal Value	Unit	Test Method		
Specific Gravity	1.39		ASTM D792		
Mechanical	Nominal Value	Unit	Test Method		
Tensile Strength (Break)	1900	psi	ASTM D638		
Tensile Elongation (Break)	380	%	ASTM D638		
Hardness	Nominal Value	Unit	Test Method		
Durometer Hardness (Shore A, 15 sec)	75		ASTM D2240		
Thermal	Nominal Value	Unit	Test Method		
Continuous Use Temperature	140	°F	ASTM D794		
Brittleness Temperature	-32.8	°F	ASTM D746		

Notes

Teknor Apex Company Corporate Headquarters

In U.S. for Vinyls, TPEs, Colorants, Engineered Thermoplastics (Chem Polymer) 505 Central Avenue

Pawtucket, Rhode Island 02861 U.S.

Phone: 401-725-8000 Fax: 401-725-8095 Toll Free (U.S. only) 800-556-3864 Teknor Apex U.K. Ltd.

Tat Bank Road

Oldbury, West Midlands B69 4NH England

Phone: (44) 121-665-2100 Fax: (44) 121-544-5530

etpsales@teknorapex.co.uk

info@teknorapex.com



Revision Date: 12/30/2016

¹ Typical properties: these are not to be construed as specifications.