

## **APEX® 85-J438-H**

## Teknor Apex Company - Flexible Polyvinyl Chloride

Friday, June 30, 2017

General Information				
General				
Material Status	Commercial: Active			
Availability	<ul><li> Africa &amp; Middle East</li><li> Asia Pacific</li></ul>	<ul><li>Europe</li><li>Latin America</li></ul>	North America	
Features	Low Gloss			
Uses	Automotive Exterior Parts			
Automotive Specifications	• GM GMP.PVC.003			
Forms	• Pellets			
Processing Method	<ul> <li>Extrusion</li> </ul>			

ASTM & ISO Properties 1				
Physical	Nominal Value Unit	Test Method		
Specific Gravity	1.40	ASTM D792		
Mechanical	Nominal Value Unit	Test Method		
Tensile Strength (Break)	2800 psi	ASTM D638		
Tensile Elongation (Break)	320 %	ASTM D638		
Hardness	Nominal Value Unit	Test Method		
Durometer Hardness (Shore D, 10 sec)	39	ASTM D2240		

## **Notes**

## Teknor Apex Company Corporate Headquarters

In U.S. for Vinyls, TPEs, Colorants, Engineered Thermoplastics (Chem Polymer) 505 Central Avenue

Pawtucket, Rhode Island 02861 U.S.

Phone: 401-725-8000 Fax: 401-725-8095

Toll Free (U.S. only) 800-556-3864

Teknor Apex U.K. Ltd.

Tat Bank Road Oldbury, West Midlands B69 4NH England

Phone: (44) 121-665-2100 Fax: (44) 121-544-5530

etpsales@teknorapex.co.uk

info@teknorapex.com



Revision Date: 12/12/2013

<sup>&</sup>lt;sup>1</sup> Typical properties: these are not to be construed as specifications.