

APEX® 85-J438A-12 Teknor Apex Company - Flexible Polyvinyl Chloride

Friday, June 30, 2017

General Information

General				
Material Status	Commercial: Active			
Availability	 Africa & Middle East Asia Pacific	EuropeLatin America	North America	
Features	Low Gloss			
Uses	Automotive Exterior Parts			
Automotive Specifications	GM GMP.PVC.003			
Forms	Pellets			

ASTM & ISO Properties¹

	•	
Physical	Nominal Value Unit	Test Method
Specific Gravity	1.28	ASTM D792
Mechanical	Nominal Value Unit	Test Method
Tensile Strength (Break)	3290 psi	ASTM D638
Tensile Elongation (Break)	380 %	ASTM D638
Hardness	Nominal Value Unit	Test Method
Durometer Hardness (Shore D, 10 sec)	38	ASTM D2240

Notes

¹ Typical properties: these are not to be construed as specifications.

Teknor Apex Company Corporate Headquarters	Teknor Apex U.K. Ltd.
	Tat Bank Road
In U.S. for Vinyls, TPEs, Colorants,	Oldbury, West Midlands B69 4NH England
Engineered Thermoplastics (Chem Polymer)	
505 Central Avenue	Phone: (44) 121-665-2100
Pawtucket, Rhode Island 02861 U.S.	Fax: (44) 121-544-5530
Phone: 401-725-8000	
Fax: 401-725-8095	etpsales@teknorapex.co.uk
Toll Free (U.S. only) 800-556-3864	

info@teknorapex.com



Revision Date: 12/12/2013

The information and recommendations contained in this bulletin are, to the best of our knowledge, accurate and reliable but no guarantee of their accuracy is made. All products are sold upon condition that purchasers shall make their own tests to determine the suitability of such products for their particular purposes and uses and purchasers assume all risks and liability for the results of use of the products, including use in accordance with seller's recommendations. Nothing in this bulletin constitutes permission or a recommendation to practice or use any invention covered by any patent owned by this company or by others. There is no warranty of merchantability and there are no other warranties for the products described.