

APEX® 78-A447R-30

Teknor Apex Company - Flexible Polyvinyl Chloride

Friday, June 30, 2017

General Information					
General					
Material Status	Commercial: Active				
Availability	 Africa & Middle East Asia Pacific	EuropeLatin America	North America		
Features	Low Gloss				
Uses	 Automotive Interior Parts 	• Knobs			
Automotive Specifications	GM GMP.PVC.023				
Forms	• Pellets				
Processing Method	Injection Molding				

ASTM & ISO Properties ¹					
Physical	Nominal Value U	Jnit	Test Method		
Specific Gravity	1.27		ASTM D792		
Mechanical	Nominal Value U	Jnit	Test Method		
Tensile Strength (Break)	1770 p	si	ASTM D638		
Tensile Elongation (Break)	350 %	6	ASTM D638		
Hardness	Nominal Value U	Jnit	Test Method		
Durometer Hardness (Shore A, 15 sec)	69		ASTM D2240		

Notes

Teknor Apex Company Corporate Headquarters

In U.S. for Vinyls, TPEs, Colorants, Engineered Thermoplastics (Chem Polymer) 505 Central Avenue Pawtucket, Rhode Island 02861 U.S.

Phone: 401-725-8000 Fax: 401-725-8095

Fax: 401-725-8095 Toll Free (U.S. only) 800-556-3864 Teknor Apex U.K. Ltd.

Tat Bank Road Oldbury, West Midlands B69 4NH England

Phone: (44) 121-665-2100 Fax: (44) 121-544-5530

etpsales@teknorapex.co.uk

info@teknorapex.com



Revision Date: 12/12/2013

¹ Typical properties: these are not to be construed as specifications.