

APEX® 76-5066-S Teknor Apex Company - Flexible Polyvinyl Chloride

Friday, June 30, 2017

General Information

General					
Material Status	Commercial: Active				
Availability	 Africa & Middle East Asia Pacific	EuropeLatin America	North America		
Features	High Gloss				
Uses	Automotive Interior Parts				
Automotive Specifications	GM GMP.PVC.040				
Forms	Pellets				
Processing Method	Injection Molding				

ASTM & ISO Properties ¹					
Physical	Nominal Value	Unit	Test Method		
Specific Gravity	1.15		ASTM D792		
Mechanical	Nominal Value	Unit	Test Method		
Tensile Strength (Break)	1450	psi	ASTM D638		
Tensile Elongation (Break)	360	%	ASTM D638		
Hardness	Nominal Value	Unit	Test Method		
Durometer Hardness (Shore A, 15 sec)	57		ASTM D2240		

Notes

¹ Typical properties: these are not to be construed as specifications.

Teknor Apex Company Corporate Headquarters

505 Central Avenue

Phone: 401-725-8000 Fax: 401-725-8095

In U.S. for Vinyls, TPEs, Colorants,

Pawtucket, Rhode Island 02861 U.S.

Toll Free (U.S. only) 800-556-3864

Engineered Thermoplastics (Chem Polymer)

Teknor Apex U.K. Ltd.

Tat Bank Road Oldbury, West Midlands B69 4NH England

Phone: (44) 121-665-2100 Fax: (44) 121-544-5530

etpsales@teknorapex.co.uk

info@teknorapex.com



Revision Date: 12/12/2013

The information and recommendations contained in this bulletin are, to the best of our knowledge, accurate and reliable but no guarantee of their accuracy is made. All products are sold upon condition that purchasers shall make their own tests to determine the suitability of such products for their particular purposes and uses and purchasers assume all risks and liability for the results of use of the products, including use in accordance with selfer's recommendations. Nothing in this bulletin constitutes permission or a recommendation to practice or use any invention covered by any patent owned by this company or by others. There is no warranty of merchantability and there are no other warranties for the products described.