

APEX[®] 69-8256-E

Teknor Apex Company - Flexible Polyvinyl Chloride

Friday, June 30, 2017

General Information

General			
Material Status	Commercial: Active		
Availability	 Africa & Middle East Asia Pacific	 Europe Latin America	North America
Features	Low Gloss		
Uses	 Automotive Interior Parts 	Profiles	Tubing
Automotive Specifications	FORD ESH-M4D292-A2		
Forms	Pellets		
Processing Method	Extrusion		

ASTM & ISO Properties ¹					
Physical	Nominal Value	Unit	Test Method		
Specific Gravity	1.25		ASTM D792		
Mechanical	Nominal Value	Unit	Test Method		
Tensile Strength (Break)	2670	psi	ASTM D638		
Tensile Elongation (Break)	400	%	ASTM D638		
Hardness	Nominal Value	Unit	Test Method		
Durometer Hardness (Shore A, 15 sec)	85		ASTM D2240		

Notes

¹ Typical properties: these are not to be construed as specifications.

Teknor Apex Company Corporate Headquarters

505 Central Avenue

In U.S. for Vinyls, TPEs, Colorants,

Pawtucket, Rhode Island 02861 U.S.

Engineered Thermoplastics (Chem Polymer)

Teknor Apex U.K. Ltd.

Tat Bank Road Oldbury, West Midlands B69 4NH England

Phone: (44) 121-665-2100 Fax: (44) 121-544-5530

etpsales@teknorapex.co.uk

Phone: 401-725-8000 Fax: 401-725-8095 Toll Free (U.S. only) 800-556-3864

info@teknorapex.com

Revision Date: 12/12/2013

The information and recommendations contained in this bulletin are, to the best of our knowledge, accurate and reliable but no guarantee of their accuracy is made. All products are sold upon condition that purchasers shall make their own tests to determine the suitability of such products for their particular purposes and uses and purchasers assume all risks and liability for the results of use of the products, including use in accordance with seller's recommendations. Nothing in this bulletin constitutes permission or a recommendation to practice or use any invention covered by any patent owned by this company or by others. There is no warranty of merchantability and there are no other warranties for the products described.