

APEX® 86-K581-A Teknor Apex Company - Flexible Polyvinyl Chloride

Friday, June 30, 2017

General Information

General			
Material Status	Commercial: Active		
Availability	 Africa & Middle East Asia Pacific	EuropeLatin America	North America
Features	High Gloss		
Uses	 Automotive Interior Parts 		
Forms	Pellets		
Processing Method	Injection Molding		

ASTM & ISO Properties ¹				
Physical	Nominal Value	Unit	Test Method	
Specific Gravity	1.19		ASTM D792	
Mechanical	Nominal Value	Unit	Test Method	
Tensile Strength (Break)	2300	psi	ASTM D638	
Tensile Elongation (Break)	400	%	ASTM D638	
Flexural Modulus	42000	psi	ASTM D790	
Hardness	Nominal Value	Unit	Test Method	
Durometer Hardness (Shore A, 15 sec)	76		ASTM D2240	
Thermal	Nominal Value	Unit	Test Method	
Continuous Use Temperature	-41.8	°F	ASTM D794	

Notes

¹ Typical properties: these are not to be construed as specifications.

Teknor Apex Company Corporate Headquarters

Teknor Apex U.K. Ltd.

Fax: (44) 121-544-5530

etpsales@teknorapex.co.uk

In U.S. for Vinyls, TPEs, Colorants, Engineered Thermoplastics (Chem Polymer) 505 Central Avenue Pawtucket, Rhode Island 02861 U.S. Tat Bank Road Oldbury, West Midlands B69 4NH England Phone: (44) 121-665-2100

Phone: 401-725-8000 Fax: 401-725-8095 Toll Free (U.S. only) 800-556-3864

info@teknorapex.com



Revision Date: 12/12/2013

The information and recommendations contained in this bulletin are, to the best of our knowledge, accurate and reliable but no guarantee of their accuracy is made. All products are sold upon condition that purchasers shall make their own tests to determine the suitability of such products for their particular purposes and uses and purchasers assume all risks and liability for the results of use of the products, including use in accordance with seller's recommendations. Nothing in this bulletin constitutes permission or a recommendation to practice or use any invention covered by any patent owned by this company or by others. There is no warranty of merchantability and there are no other warranties for the products described.