

APEX® 77-W385-A

Teknor Apex Company - Flexible Polyvinyl Chloride

Friday, June 30, 2017

General Information						
Product Description						
The Nissan Automotive Specification	on is Suggested, not Approved.					
General						
Material Status	Commercial: Active					
Availability	 Africa & Middle East Asia Pacific	EuropeLatin America	North America			
Features	Low Gloss	Low Temperature Flexibility				
Uses	 Automotive Interior Parts 	Automotive Interior Parts				
RoHS Compliance	 RoHS Compliant 					
Automotive Specifications	NISSAN NES D5311-VT2					
Appearance	• Opaque					
Forms	• Pellets					
Processing Method	 Extrusion 					

ASTM & ISO Properties 1					
Physical	Nominal Value	Unit	Test Method		
Specific Gravity	1.30		ASTM D792		
Mechanical	Nominal Value	Unit	Test Method		
Tensile Strength (Break)	2250	psi	ASTM D638		
Tensile Elongation (Break)	410	%	ASTM D638		
Hardness	Nominal Value	Unit	Test Method		
Durometer Hardness (Shore A, 15 sec)	75		ASTM D2240		
Thermal	Nominal Value	Unit	Test Method		
Brittleness Temperature	-52.6	°F	ASTM D746		

Notes

Teknor Apex Company Corporate Headquarters

In U.S. for Vinyls, TPEs, Colorants, Engineered Thermoplastics (Chem Polymer)

505 Central Avenue

Pawtucket, Rhode Island 02861 U.S.

Phone: 401-725-8000 Fax: 401-725-8095

Toll Free (U.S. only) 800-556-3864

Teknor Apex U.K. Ltd.

Tat Bank Road

Oldbury, West Midlands B69 4NH England

Phone: (44) 121-665-2100 Fax: (44) 121-544-5530

etpsales@teknorapex.co.uk

info@teknorapex.com



Revision Date: 12/12/2013

¹ Typical properties: these are not to be construed as specifications.