

# Chemion® 125 GH

## Teknor Apex Company (Chem Polymer) - Polyamide 66

Friday, June 30, 2017

General Information					
General					
Material Status	<ul> <li>Commercial: Active</li> </ul>				
Availability	Asia Pacific	• Europe	North America		
Filler / Reinforcement	Glass Fiber, 25% Filler by Weight				
Additive	Heat Stabilizer	<ul> <li>Lubricant</li> </ul>			
Features	<ul><li>Good Dimensional Stability</li><li>Good Processability</li></ul>	<ul><li> Good Toughness</li><li> Heat Stabilized</li></ul>	<ul><li>High Strength</li><li>Lubricated</li></ul>		
Appearance	Black	<ul> <li>Natural Color</li> </ul>			
Forms	• Pellets				
Processing Method	<ul> <li>Injection Molding</li> </ul>				

ASTM & ISO Properties 1				
Physical	Nominal Value	Unit	Test Method	
Specific Gravity	1.33		ASTM D792	
Molding Shrinkage - Flow	4.0E-3	in/in	ASTM D955	
Water Absorption (24 hr)	0.80	%	ASTM D570	
Mechanical	Nominal Value	Unit	Test Method	
Tensile Strength	20000	psi	ASTM D638	
Tensile Elongation (Break)	2.0	%	ASTM D638	
Flexural Modulus	900000	psi	ASTM D790	
Flexural Strength	28000	psi	ASTM D790	
Impact	Nominal Value	Unit	Test Method	
Notched Izod Impact (73°F)	1.2	ft·lb/in	ASTM D256	
Thermal	Nominal Value	Unit	Test Method	
Deflection Temperature Under Load			ASTM D648	
264 psi, Unannealed	433	°F		
Melting Temperature	490	°F		

Processing Information				
Injection	Nominal Value	Unit		
Drying Temperature	150 to 180	°F		
Suggested Max Moisture	0.20	%		
Rear Temperature	560	°F		
Middle Temperature	540	°F		
Front Temperature	530	°F		
Nozzle Temperature	530	°F		
Mold Temperature	140 to 200	°F		
Injection Pressure	5000 to 20000	psi		
Screw Speed	60 to 120	rpm支有以及分销商 科技。现分销商		
Notes	い物塑化	等次是1021-500		
<sup>1</sup> Typical properties: these are not to be construed as specifications.	上海松粉PEX常	M 联系图片		
	TEKNOrapex.shs.	psi		

#### **Notes**

Revision Date: 12/11/2008

<sup>&</sup>lt;sup>1</sup> Typical properties: these are not to be construed as specifications.

### Chemlon® 125 GH

### Teknor Apex Company (Chem Polymer) - Polyamide 66

Teknor Apex Company Corporate Headquarters

In U.S. for Vinyls, TPEs, Colorants, Engineered Thermoplastics (Chem Polymer) 505 Central Avenue

Pawtucket, Rhode Island 02861 U.S.

Phone: 401-725-8000 Fax: 401-725-8095

Toll Free (U.S. only) 800-556-3864

info@teknorapex.com

Teknor Apex U.K. Ltd.

Tat Bank Road Oldbury, West Midlands B69 4NH England

Phone: (44) 121-665-2100 Fax: (44) 121-544-5530

etpsales@teknorapex.co.uk



Revision Date: 12/11/2008