

Chemlon® 109-33 GH

Teknor Apex Company (Chem Polymer) - Polyamide 66

Friday, June 30, 2017

General Information					
General					
Material Status	Commercial: Active				
Availability	Asia Pacific	• Europe	 North America 		
Filler / Reinforcement	Glass Fiber, 33% Filler by Weight				
Additive	 Heat Stabilizer 				
Features	 Creep Resistant Good Impact Resistance Good Processability	Good StiffnessGood ToughnessHeat Stabilized	High Strength		
Appearance	• Black	 Natural Color 			
Forms	• Pellets				
Processing Method	 Injection Molding 				

ASTM & ISO Properties ¹			
Physical	Nominal Value	Unit	Test Method
Specific Gravity	1.34		ASTM D792
Molding Shrinkage - Flow	3.0E-3	in/in	ASTM D955
Water Absorption (24 hr)	0.80	%	ASTM D570
Mechanical	Nominal Value	Unit	Test Method
Tensile Strength	20000	psi	ASTM D638
Tensile Elongation (Break)	3.0	%	ASTM D638
Flexural Modulus	1.00E+6	psi	ASTM D790
Flexural Strength	29500	psi	ASTM D790
Impact	Nominal Value	Unit	Test Method
Notched Izod Impact (73°F)	3.0	ft·lb/in	ASTM D256
Thermal	Nominal Value	Unit	Test Method
Deflection Temperature Under Load			ASTM D648
264 psi, Unannealed	475	°F	
Melting Temperature	490	°F	

Processing Information				
Injection	Nominal Value Unit			
Drying Temperature	150 to 180 °F			
Suggested Max Moisture	0.20 %			
Rear Temperature	560 °F			
Middle Temperature	540 °F			
Front Temperature	530 °F			
Nozzle Temperature	530 °F			
Mold Temperature	140 to 200 °F			
Injection Pressure	140 to 200 °F 5000 to 20000 psi			
Screw Speed	5000 to 20000 psi 60 to 120 ppm 文 报为 60 to 120 ppm 文 报为 FEKNOR APEX 特诺尔基原 021-58958519 TEKNOR APEX 特诺尔基原 021-58958519			
Notes	大大大大大大大大大大大大大大大大大大大大大大大大大大大大大大大大大大大大大			
¹ Typical properties: these are not to be construed as specifications.	TEKNOR AFFICONI			
	teknoter			

Notes

Revision Date: 12/11/2008

¹ Typical properties: these are not to be construed as specifications.

Chemlon® 109-33 GH

Teknor Apex Company (Chem Polymer) - Polyamide 66

Teknor Apex Company Corporate Headquarters

In U.S. for Vinyls, TPEs, Colorants, Engineered Thermoplastics (Chem Polymer) 505 Central Avenue

Pawtucket, Rhode Island 02861 U.S.

Phone: 401-725-8000 Fax: 401-725-8095

Toll Free (U.S. only) 800-556-3864

info@teknorapex.com

Teknor Apex U.K. Ltd.

Tat Bank Road Oldbury, West Midlands B69 4NH England

Phone: (44) 121-665-2100 Fax: (44) 121-544-5530

etpsales@teknorapex.co.uk



Revision Date: 12/11/2008