

Medalist® MD-53278 (PRELIMINARY DATA)

Teknor Apex Company - Thermoplastic Elastomer

Friday, June 30, 2017

General Information

Product Description

The Medalist MD-53200 Series is a high performance thermoplastic elastomer series, designed to be a sustainable alternative to flexible PVC for medical tubing and film. Medalist MD-53278 is a low density, medium hardness, clear, lubricated grade, available in Nat and color-matched, intended for use in medical and healthcare applications, with excellent processability and throughput in extruded tubing.

General

| | | | |
|-------------------|---|--|---|
| Material Status | • Preliminary Data | | |
| Availability | • Africa & Middle East • Asia Pacific | • Europe • Latin America | • North America |
| Features | • Autoclave Sterilizable • Chemical Resistant • Ethylene Oxide Sterilizable • Good Adhesion • Good Colorability • Good Melt Strength | • Good Processability • Good Toughness • Halogen Free • High Clarity • High Purity • Kink Resistant | • Low Density • Low Specific Gravity • Lubricated • Medium Hardness • No Animal Derived Components • Radiation (Gamma) Resistant |
| Uses | • Clear Sheet • Film • Hose | • Medical/Healthcare Applications • Pharmaceuticals • Rubber Replacement | • Tubing |
| Agency Ratings | • ISO 10993 Part 5 | • ISO 13485 | |
| RoHS Compliance | • RoHS Compliant | | |
| Appearance | • Clear/Transparent | • Colors Available | |
| Forms | • Pellets | | |
| Processing Method | • Cast Film | • Extrusion | • Injection Molding |

ASTM & ISO Properties ¹

| Physical | Nominal Value | Unit | Test Method |
|--|---------------|----------|-------------|
| Specific Gravity | 0.890 | | ASTM D792 |
| Melt Mass-Flow Rate (MFR) (200°C/5.0 kg) | 7.0 | g/10 min | ASTM D1238 |
| Elastomers | Nominal Value | Unit | Test Method |
| Tensile Stress (50% Strain) | 645 | psi | ASTM D412 |
| Tensile Stress (100% Strain) | 695 | psi | ASTM D412 |
| Tensile Stress (300% Strain) | 980 | psi | ASTM D412 |
| Tensile Strength (Break) | 2170 | psi | ASTM D412 |
| Tensile Elongation (Break) | 620 | % | ASTM D412 |
| Tear Strength | 367 | lbf/in | ASTM D624 |
| Compression Set | | | ASTM D395 |
| 73°F, 22 hr | 23 | % | |
| 158°F, 22 hr | 83 | % | |
| Hardness | Nominal Value | Unit | Test Method |
| Durometer Hardness | | | ASTM D2240 |
| Shore A, 1 sec | 81 | | |
| Shore A, 5 sec | 79 | | |

上海松翰塑化科技有限公司
TEKNOR APEX 特诺尔爱佩斯 一级分销商
teknapex.shshj.com 联系电话: 021-58958519

Revision Date: 4/2/2017

The information and recommendations contained in this bulletin are, to the best of our knowledge, accurate and reliable but no guarantee of their accuracy is made. All products are sold upon condition that purchasers shall make their own tests to determine the suitability of such products for their particular purposes and uses and purchasers assume all risks and liability for the results of use of the products, including use in accordance with seller's recommendations. Nothing in this bulletin constitutes permission or a recommendation to practice or use any invention covered by any patent owned by this company or by others. There is no warranty of merchantability and there are no other warranties for the products described.

Medalist® MD-53278 (PRELIMINARY DATA)

Teknor Apex Company - Thermoplastic Elastomer

Legal Statement

The information and recommendations contained in this bulletin are, to the best of our knowledge, accurate and reliable but no guarantee of their accuracy is made. All products are sold upon condition that purchasers shall make their own tests to determine the suitability of such products for their particular purposes and uses and purchaser assumes all risks and liability for the results of use of the products, including use in accordance with seller's recommendations. Nothing in this bulletin constitutes permission or a recommendation to practice or use any invention covered by any patent owned by this company or others. There is no warranty of merchantability and there are no other warranties for the products described. For detailed Product Stewardship information, please contact us. Any product of Teknor Apex, including product names, shall not be used or tested in medical or food contact applications without the prior written acknowledgement of Teknor Apex as to the intended use. Please note that some products may not be available in one or more countries.

Processing Information

| Injection | Nominal Value | Unit |
|------------------------|---------------|------|
| Rear Temperature | 300 to 340 | °F |
| Middle Temperature | 340 to 380 | °F |
| Front Temperature | 380 to 440 | °F |
| Nozzle Temperature | 380 to 440 | °F |
| Processing (Melt) Temp | 380 to 440 | °F |
| Mold Temperature | 70 to 125 | °F |
| Back Pressure | 50.0 to 150 | psi |
| Screw Speed | 50 to 100 | rpm |
| Cushion | 0.140 to 1.00 | in |

Injection Notes

Drying is not necessary. However, if moisture is a problem, dry the pellets for 2 to 4 hours at 150°F (65°C).

| Extrusion | Nominal Value | Unit |
|-----------------------|---------------|------|
| Cylinder Zone 1 Temp. | 320 to 370 | °F |
| Cylinder Zone 2 Temp. | 360 to 385 | °F |
| Cylinder Zone 3 Temp. | 360 to 400 | °F |
| Cylinder Zone 4 Temp. | 360 to 400 | °F |
| Cylinder Zone 5 Temp. | 360 to 410 | °F |
| Die Temperature | 350 to 420 | °F |

Extrusion Notes

Screw Speed: 30 to 100 rpm.

Screen Pack Recommendation:

60/200/200/60 to 60/200/400/400/200/60 mesh size.

Notes

¹ Typical properties: these are not to be construed as specifications.

Teknor Apex Company Corporate Headquarters

In U.S. for Vinyls, TPEs, Colorants,
Engineered Thermoplastics (Chem Polymer)
505 Central Avenue
Pawtucket, Rhode Island 02861 U.S.

Phone: 401-725-8000
Fax: 401-725-8095
Toll Free (U.S. only) 800-556-3864

info@teknorapex.com

Teknor Apex U.K. Ltd.

Tat Bank Road
Oldbury, West Midlands B69 4NH England

Phone: (44) 121-665-2100
Fax: (44) 121-544-5530

etpsales@teknorapex.co.uk



Revision Date: 4/2/2017

The information and recommendations contained in this bulletin are, to the best of our knowledge, accurate and reliable but no guarantee of their accuracy is made. All products are sold upon condition that purchasers shall make their own tests to determine the suitability of such products for their particular purposes and uses and purchasers assume all risks and liability for the results of use of the products, including use in accordance with seller's recommendations. Nothing in this bulletin constitutes permission or a recommendation to practice or use any invention covered by any patent owned by this company or by others. There is no warranty of merchantability and there are no other warranties for the products described.