

APEX® 3080

Teknor Apex Company - Flexible Polyvinyl Chloride

Friday, June 30, 2017

General Information					
General					
Material Status	Commercial: Active				
Availability	 Africa & Middle East 	• Europe	North America		
	 Asia Pacific 	 Latin America 	North America		
Features	 General Purpose 				
Llege	• Film	• Hose	• Tubing		
Uses	 General Purpose 	 Sheet 			
Appearance	 Natural Color 	 Opaque 			
Forms	• Pellets				
Processing Method	Extrusion				

ASTM & ISO Properties ¹					
Physical	Nominal Value	Unit	Test Method		
Specific Gravity	1.40		ASTM D792		
Mechanical	Nominal Value	Unit	Test Method		
Tensile Strength (100% Strain)	1020	psi	ASTM D638		
Tensile Strength (Break)	2190	psi	ASTM D638		
Tensile Elongation (Break)	380	%	ASTM D638		
Elastomers	Nominal Value	Unit	Test Method		
Tear Strength ²	295	lbf/in	ASTM D624		
Hardness	Nominal Value	Unit	Test Method		
Durometer Hardness			ASTM D2240		
Shore A	86				
Shore A, 15 sec	80				
Thermal	Nominal Value	Unit	Test Method		
Brittleness Temperature	-22.0	°F	ASTM D746		

Notes

Teknor Apex Company Corporate Headquarters

In U.S. for Vinyls, TPEs, Colorants, Engineered Thermoplastics (Chem Polymer)

505 Central Avenue

Pawtucket, Rhode Island 02861 U.S.

Phone: 401-725-8000 Fax: 401-725-8095

Toll Free (U.S. only) 800-556-3864

info@teknorapex.com

Teknor Apex U.K. Ltd.

Tat Bank Road

Oldbury, West Midlands B69 4NH England

Phone: (44) 121-665-2100 Fax: (44) 121-544-5530

etpsales@teknorapex.co.uk



Revision Date: 12/12/2013

¹ Typical properties: these are not to be construed as specifications.

² Die C