

APEX® 155-Y

Teknor Apex Company - Flexible Polyvinyl Chloride

Friday, June 30, 2017

General Information					
General					
Material Status	Commercial: Active				
Availability	Africa & Middle EastAsia Pacific	EuropeLatin America	North America		
Features	 Sunlight Resistant (720 hours) 	UV Resistant			
Uses	Cable Jacketing	Wire & Cable Applications	Wire Jacketing		
Wire Types	• NMB	• SEC			
Agency Ratings	• UL QMTT2				
RoHS Compliance	RoHS Compliant				
Appearance	Opaque				
Forms	• Pellets				

ASTM & ISO Properties 1					
Physical	Nominal Value	Unit	Test Method		
Specific Gravity	1.42		ASTM D792		
Mechanical	Nominal Value	Unit	Test Method		
Tensile Strength (Break)	2120	psi	ASTM D638		
Tensile Elongation (Break)	280	%	ASTM D638		
Hardness	Nominal Value	Unit	Test Method		
Durometer Hardness (Shore A, 15 sec)	81		ASTM D2240		
Thermal	Nominal Value	Unit	Test Method		
Continuous Use Temperature	167	°F	ASTM D794		
Additional Information					

Additional Information

Sunlight Resistant only available in gray or black.

Notes

Teknor Apex Company Corporate Headquarters

In U.S. for Vinyls, TPEs, Colorants, Engineered Thermoplastics (Chem Polymer)

505 Central Avenue

Pawtucket, Rhode Island 02861 U.S.

Phone: 401-725-8000 Fax: 401-725-8095

Toll Free (U.S. only) 800-556-3864

Teknor Apex U.K. Ltd.

Tat Bank Road

Oldbury, West Midlands B69 4NH England

Phone: (44) 121-665-2100

Fax: (44) 121-544-5530

etpsales@teknorapex.co.uk

info@teknorapex.com



Revision Date: 12/12/2013

¹ Typical properties: these are not to be construed as specifications.