

APEX® 3202-80NT

Teknor Apex Company - Flexible Polyvinyl Chloride

Friday, June 30, 2017

General Information					
General					
Material Status	Commercial: Active				
Availability	 Africa & Middle East Asia Pacific	EuropeLatin America	North America		
Additive	Plasticizer				
Features	Ethylene Oxide Sterilizable	 Non-Phthalate - Citrate Plasticizer 			
Uses	CapsConnectors	Food Service ApplicationsSafety Equipment	Valves/Valve Parts		
Appearance	 Clear/Transparent 				
Forms	• Pellets				
Processing Method	Injection Molding				

ASTM & ISO Properties ¹				
Physical	Nominal Value	Unit	Test Method	
Specific Gravity	1.24		ASTM D792	
Mechanical	Nominal Value	Unit	Test Method	
Tensile Strength (Break)	2750	psi	ASTM D638	
Tensile Elongation (Break)	360	%	ASTM D638	
Hardness	Nominal Value	Unit	Test Method	
Durometer Hardness (Shore A, 15 sec)	80		ASTM D2240	
Thermal	Nominal Value	Unit	Test Method	
Brittleness Temperature	-5.80	°F	ASTM D746	

Notes

Teknor Apex Company Corporate Headquarters

In U.S. for Vinyls, TPEs, Colorants, Engineered Thermoplastics (Chem Polymer) 505 Central Avenue Pawtucket, Rhode Island 02861 U.S.

Phone: 401-725-8000

Fax: 401-725-8095 Toll Free (U.S. only) 800-556-3864 Teknor Apex U.K. Ltd.

Tat Bank Road

Oldbury, West Midlands B69 4NH England

Phone: (44) 121-665-2100 Fax: (44) 121-544-5530

etpsales@teknorapex.co.uk

info@teknorapex.com



Revision Date: 12/12/2013

¹ Typical properties: these are not to be construed as specifications.