

APEX® 93-A0591C-97

Teknor Apex Company - Flexible Polyvinyl Chloride

Friday, June 30, 2017

General Information				
General				
Material Status	Commercial: Active			
Availability	 Africa & Middle East Asia Pacific	EuropeLatin America	North America	
Uses	 Transportation Wire Insula 	tion		
Wire Types	• GPT			
Agency Ratings	• SAE J1128			
Forms	• Pellets			
Processing Method	 Extrusion 			

ASTM & ISO Properties 1				
Nominal Value	Unit	Test Method		
1.33		ASTM D792		
Nominal Value	Unit	Test Method		
2670	psi	ASTM D638		
290	%	ASTM D638		
Nominal Value	Unit	Test Method		
72		ASTM D2240		
Nominal Value	Unit	Test Method		
221	°F	ASTM D794		
-0.400	°F	ASTM D746		
Nominal Value	Unit	Test Method		
2.0E+14	ohms·cm	ASTM D257		
Nominal Value	Unit	Test Method		
26	%	ASTM D2863		
	Nominal Value 1.33 Nominal Value 2670 290 Nominal Value 72 Nominal Value 221 -0.400 Nominal Value 2.0E+14 Nominal Value	Nominal Value Unit 1.33 Nominal Value Unit 2670 psi 290 % Nominal Value Unit		

Additional Information

Temperature Rating: 105 °C

Ultimate Elongation Retained, UL 1581, Oven Aged, 7 days, 136°C: 93 % Tensile Strength Retained, UL 1581, Oven Aged, 7 days, 136°C: 95 %

Processing	Information
------------	-------------

Extrusion	Nominal Value Unit
Melt Temperature	375 °F

Notes

Teknor Apex Company Corporate Headquarters

In U.S. for Vinyls, TPEs, Colorants, Engineered Thermoplastics (Chem Polymer)

505 Central Avenue

Pawtucket, Rhode Island 02861 U.S.

Phone: 401-725-8000 Fax: 401-725-8095

Toll Free (U.S. only) 800-556-3864

Teknor Apex U.K. Ltd.

Oldbury, West Midlands B69 4NH England

Phone: (44) 121-665-2100 Fax: (44) 121-544-5530

etpsales@teknorapex.co.uk

info@teknorapex.com

上海松前理化科技有限公司 TEKNOR APEX 特诺尔曼佩斯 021-58958519 teknorapex.shshsj.com 麻素患语: 021-58958519

Revision Date: 12/12/2013

¹ Typical properties: these are not to be construed as specifications.