

APEX® 65001 Teknor Apex Company - Flexible Polyvinyl Chloride

Friday, June 30, 2017

General Information

General				
Material Status	Commercial: Active			
Availability	 Africa & Middle East Asia Pacific	EuropeLatin America	North America	
Features	 Flame Retardant 			
Uses	Communication Wire Jacketing			
Wire Types	• CL2 • CL3	• CM • FPL	• MP • OFN	
Agency Ratings	NEC Article 725NEC Article 760NEC Article 770	NEC Article 800UL 13UL 1424	• UL 444	
RoHS Compliance	 RoHS Compliant 			
Appearance	Opaque			
Forms	Pellets			
Processing Method	Extrusion			

ASTM & ISO Properties ¹					
Physical	Nominal Value	Unit	Test Method		
Specific Gravity	1.37		ASTM D792		
Mechanical	Nominal Value	Unit	Test Method		
Tensile Strength (Break)	3350	psi	ASTM D638		
Tensile Elongation (Break)	260	%	ASTM D638		
Hardness	Nominal Value	Unit	Test Method		
Durometer Hardness (Shore C, 10 sec)	70		ASTM D2240		
Thermal	Nominal Value	Unit	Test Method		
Continuous Use Temperature	167	°F	ASTM D794		
Brittleness Temperature	-22.0	°F	ASTM D746		
Flammability	Nominal Value	Unit	Test Method		
Oxygen Index	32	%	ASTM D2863		
Additional Information					

Non-lead

Formerly 95-A0532A-95

Temperature Rating: 75 °C

UL Sunlight Resistance Recognition: No



Revision Date: 12/12/2013

The information and recommendations contained in this bulletin are, to the best of our knowledge, accurate and reliable but no guarantee of their accuracy is made. All products are sold upon condition that purchasers shall make their own tests to determine the suitability of such products for their particular purposes and uses and purchasers assume all risks and liability for the results of use of the products, including use in accordance with seller's recommendations. Nothing in this bulletin constitutes permission or a recommendation to practice or use any invention covered by any patent owned by this company or by others. There is no warranty of merchantability and there are no other warranties for the products described.

APEX® 65001

Teknor Apex Company Corporate Headquarters

In U.S. for Vinyls, TPEs, Colorants, Engineered Thermoplastics (Chem Polymer) 505 Central Avenue Pawtucket, Rhode Island 02861 U.S.

Phone: 401-725-8000 Fax: 401-725-8095 Toll Free (U.S. only) 800-556-3864

info@teknorapex.com

Teknor Apex Company - Flexible Polyvinyl Chloride

Teknor Apex U.K. Ltd.

Tat Bank Road Oldbury, West Midlands B69 4NH England

Phone: (44) 121-665-2100 Fax: (44) 121-544-5530

etpsales@teknorapex.co.uk



Revision Date: 12/12/2013

The information and recommendations contained in this bulletin are, to the best of our knowledge, accurate and reliable but no guarantee of their accuracy is made. All products are sold upon condition that purchasers shall make their own tests to determine the suitability of such products for their particular purposes and uses and purchasers assume all risks and liability for the results of use of the products, including use in accordance with seller's recommendations. Nothing in this bulletin constitutes permission or a recommendation to practice or use any invention covered by any patent owned by this company or by others. There is no warranty of merchantability and there are no other warranties for the products described.