

# APEX® 78-A272-A Teknor Apex Company - Flexible Polyvinyl Chloride

Friday, June 30, 2017

### **General Information**

General			
Material Status	Commercial: Active		
Availability	<ul><li> Africa &amp; Middle East</li><li> Asia Pacific</li></ul>	<ul><li>Europe</li><li>Latin America</li></ul>	North America
Features	<ul> <li>Flame Retardant</li> </ul>		
Uses	Cable Jacketing		
Wire Types	• CL2	• CL3	• CMP
Agency Ratings	NEC Article 725	NEC Article 800	
RoHS Compliance	<ul> <li>RoHS Compliant</li> </ul>		
Appearance	Clear/Transparent		
Forms	Pellets		
Processing Method	Extrusion		

ASTM & ISO Properties <sup>1</sup>				
Physical	Nominal Value	Unit	Test Method	
Specific Gravity	1.24		ASTM D792	
Mechanical	Nominal Value	Unit	Test Method	
Tensile Strength (Break)	2560	psi	ASTM D638	
Tensile Elongation (Break)	340	%	ASTM D638	
Hardness	Nominal Value	Unit	Test Method	
Durometer Hardness (Shore A, 15 sec)	84		ASTM D2240	
Thermal	Nominal Value	Unit	Test Method	
Continuous Use Temperature	194	°F	ASTM D794	
Brittleness Temperature	-25.6	°F	ASTM D746	
Flammability	Nominal Value	Unit	Test Method	
Oxygen Index	27	%	ASTM D2863	
Additional Information				

Temperature Rating: 90 °C

UL Sunlight Resistance Recognition: No

Ultimate Elongation Retained, UL 1581, Oven Aged, 7 days, 121°C: 80 % Tensile Strength Retained, UL 1581, Oven Aged, 7 days, 121°C: 107 %

Processing Information			
Extrusion	Nominal Value Unit		
Melt Temperature	355 °F		
Notes			
<sup>1</sup> Typical properties: these are not to be construed as specifications.	司公司		
	上海松翰裡化科技有限公共 上海松翰建化科技有限公共 TEKNOR APEX特诺尔爱佩斯一级分销商 TEKNOR APEX特诺尔爱佩斯级分销商 17EKNOR APEX特诺尔爱佩斯		
	一代前望化市家餐園町21-5895		
	Light APEX to mission		
	TEKNOrapex.sno		
	10.		

The information and recommendations contained in this bulletin are, to the best of our knowledge, accurate and reliable but no guarantee of their accuracy is made. All products are sold upon condition that purchasers shall make their own tests to determine the suitability of such products for their particular purposes and uses and purchasers assume all risks and liability for the results of use of the products, including use in accordance with seller's recommendations. Nothing in this bulletin constitutes permission or a recommendation to practice or use any invention covered by any patent owned by this company or by others. There is no warranty of merchantability and there are no other warranties for the products described.

## APEX® 78-A272-A

### Teknor Apex Company Corporate Headquarters

In U.S. for Vinyls, TPEs, Colorants, Engineered Thermoplastics (Chem Polymer) 505 Central Avenue Pawtucket, Rhode Island 02861 U.S.

Phone: 401-725-8000 Fax: 401-725-8095 Toll Free (U.S. only) 800-556-3864

info@teknorapex.com

### Teknor Apex Company - Flexible Polyvinyl Chloride

Teknor Apex U.K. Ltd.

Tat Bank Road Oldbury, West Midlands B69 4NH England

Phone: (44) 121-665-2100 Fax: (44) 121-544-5530

etpsales@teknorapex.co.uk



Revision Date: 12/12/2013

The information and recommendations contained in this bulletin are, to the best of our knowledge, accurate and reliable but no guarantee of their accuracy is made. All products are sold upon condition that purchasers shall make their own tests to determine the suitability of such products for their particular purposes and uses and purchasers assume all risks and liability for the results of use of the products, including use in accordance with seller's recommendations. Nothing in this bulletin constitutes permission or a recommendation to practice or use any invention covered by any patent owned by this company or by others. There is no warranty of merchantability and there are no other warranties for the products described.