

# APEX® 7500-90

### Teknor Apex Company - Flexible Polyvinyl Chloride

Friday, June 30, 2017

### **General Information**

Material Status	<ul> <li>Commercial: Active</li> </ul>		
Availability	<ul><li> Africa &amp; Middle East</li><li> Asia Pacific</li></ul>	<ul><li>Europe</li><li>Latin America</li></ul>	North America
Features	High Heat Resistance		
Uses	<ul><li>Connectors</li><li>Grommets</li></ul>	<ul><li> Plugs</li><li> Strain Reliefs</li></ul>	
Wire Types	<ul> <li>Molded Components</li> </ul>		
Agency Ratings	UL QMFZ2		
RoHS Compliance	<ul> <li>RoHS Compliant</li> </ul>		
Appearance	Clear/Transparent		
Forms	Pellets		
Processing Method	<ul> <li>Injection Molding</li> </ul>		

ASTM & ISO Properties <sup>1</sup>				
Physical	Nominal Value	Unit	Test Method	
Specific Gravity	1.24		ASTM D792	
Molding Shrinkage - Flow	0.010 to 0.012	in/in	ASTM D955	
Mechanical	Nominal Value	Unit	Test Method	
Tensile Strength (Break)	3000	psi	ASTM D638	
Tensile Elongation (Break)	230	%	ASTM D638	
Hardness	Nominal Value	Unit	Test Method	
Durometer Hardness (Shore C, 10 sec)	65		ASTM D2240	
Thermal	Nominal Value	Unit	Test Method	
Continuous Use Temperature	221	°F	ASTM D794	
Brittleness Temperature	-18.4	°F	ASTM D746	
RTI Elec (0.06 in)	122	°F	UL 746	
RTI Imp (0.06 in)	122	°F	UL 746	
RTI Str (0.06 in)	122	°F	UL 746	
Flammability	Nominal Value	Unit	Test Method	
Flame Rating (0.06 in)	HB		UL 94	
Oxygen Index	23	%	ASTM D2863	
Additional Information				

Temperature Rating: 105 °C

# Processing Information Injection Nominal Value Unit Processing (Melt) Temp 380 °F Notes Notes Notes Notes 1 Typical properties: these are not to be construed as specifications. Image: Construct as specifications. Image: Construct as specifications.

Revision Date: 12/12/2013

The information and recommendations contained in this bulletin are, to the best of our knowledge, accurate and reliable but no guarantee of their accuracy is made. All products are sold upon condition that purchasers shall make their own tests to determine the suitability of such products for their particular purposes and uses and purchasers assume all risks and liability for the results of use of the products, including use in accordance with seller's recommendations. Nothing in this bulletin constitutes permission or a recommendation to practice or use any invention covered by any patent owned by this company or by others. There is no warranty of merchantability and there are no other warranties for the products described.

# APEX® 7500-90

### Teknor Apex Company Corporate Headquarters

In U.S. for Vinyls, TPEs, Colorants, Engineered Thermoplastics (Chem Polymer) 505 Central Avenue Pawtucket, Rhode Island 02861 U.S.

Phone: 401-725-8000 Fax: 401-725-8095 Toll Free (U.S. only) 800-556-3864

info@teknorapex.com

## Teknor Apex Company - Flexible Polyvinyl Chloride

Teknor Apex U.K. Ltd.

Tat Bank Road Oldbury, West Midlands B69 4NH England

Phone: (44) 121-665-2100 Fax: (44) 121-544-5530

etpsales@teknorapex.co.uk



Revision Date: 12/12/2013

The information and recommendations contained in this bulletin are, to the best of our knowledge, accurate and reliable but no guarantee of their accuracy is made. All products are sold upon condition that purchasers shall make their own tests to determine the suitability of such products for their particular purposes and uses and purchasers assume all risks and liability for the results of use of the products, including use in accordance with seller's recommendations. Nothing in this bulletin constitutes permission or a recommendation to practice or use any invention covered by any patent owned by this company or by others. There is no warranty of merchantability and there are no other warranties for the products described.