

APEX® 3095-H

Teknor Apex Company - Flexible Polyvinyl Chloride

Friday, June 30, 2017

	General Information			
General				
Material Status	Commercial: Active			
Availability	 Africa & Middle East Asia Pacific	EuropeLatin America	North America	
Uses	General PurposeHose	 Profiles Tubing		
Appearance	 Natural Color 	Opaque		
Forms	• Pellets			
Processing Method	 Extrusion 			

ASTM & ISO Properties ¹					
Physical	Nominal Value	Unit	Test Method		
Specific Gravity	1.40		ASTM D792		
Mechanical	Nominal Value	Unit	Test Method		
Tensile Strength (Break)	2900	psi	ASTM D638		
Tensile Elongation (Break)	300	%	ASTM D638		
Hardness	Nominal Value	Unit	Test Method		
Durometer Hardness			ASTM D2240		
Shore C	81				
Shore C, 10 sec	70				
Thermal	Nominal Value	Unit	Test Method		
Brittleness Temperature	14.0	°F	ASTM D746		

Notes

Teknor Apex Company Corporate Headquarters

In U.S. for Vinyls, TPEs, Colorants, Engineered Thermoplastics (Chem Polymer) 505 Central Avenue

Pawtucket, Rhode Island 02861 U.S.

Phone: 401-725-8000 Fax: 401-725-8095

Toll Free (U.S. only) 800-556-3864

Teknor Apex U.K. Ltd.

Tat Bank Road

Oldbury, West Midlands B69 4NH England

Phone: (44) 121-665-2100 Fax: (44) 121-544-5530

etpsales@teknorapex.co.uk

info@teknorapex.com



Revision Date: 12/30/2016

¹ Typical properties: these are not to be construed as specifications.