

Flexalloy® 9750-55

Teknor Apex Company - Polyvinyl Chloride Elastomer

Friday, June 30, 2017

General Information				
General				
Material Status	Commercial: Active			
Availability	 Africa & Middle East Asia Pacific	EuropeLatin America	North America	
Features	Low Gloss	Ultra High Molecular Weight		
Forms	Pellets			

Nominal Value	Unit	Test Method
1.19		ASTM D792
Nominal Value	Unit	Test Method
620	psi	ASTM D638
1630	psi	ASTM D638
360	%	ASTM D638
Nominal Value	Unit	Test Method
150	lbf/in	ASTM D624
Nominal Value	Unit	Test Method
55		ASTM D2240
Nominal Value	Unit	Test Method
176	°F	ASTM D794
	Nominal Value 55 Nominal Value	Nominal Value Unit 150 lbf/in Nominal Value Unit 55 Nominal Value Unit 176 °F

Notes

Teknor Apex Company Corporate Headquarters

In U.S. for Vinyls, TPEs, Colorants, Engineered Thermoplastics (Chem Polymer) 505 Central Avenue Pawtucket, Rhode Island 02861 U.S.

Phone: 401-725-8000

Fax: 401-725-8095

Toll Free (U.S. only) 800-556-3864

Teknor Apex U.K. Ltd.

Tat Bank Road Oldbury, West Midlands B69 4NH England

Phone: (44) 121-665-2100 Fax: (44) 121-544-5530

etpsales@teknorapex.co.uk

info@teknorapex.com



Revision Date: 12/12/2013

¹ Typical properties: these are not to be construed as specifications.