

## **APEX® 60003**

## Teknor Apex Company - Flexible Polyvinyl Chloride

Friday, June 30, 2017

General Information					
General					
Material Status	Commercial: Active				
Availability	<ul> <li>Africa &amp; Middle East</li> </ul>	• Europe	North America		
	<ul> <li>Asia Pacific</li> </ul>	<ul> <li>Latin America</li> </ul>			
Features	<ul> <li>Flame Retardant</li> </ul>				
Uses	Communication Wire Insulation				
Wire Types	• CL2R	• CMR	• MPR		
	• CL3R	• FPLR	• OFNR		
Agency Ratings	<ul> <li>NEC Article 725</li> </ul>	<ul> <li>NEC Article 800</li> </ul>			
	<ul> <li>NEC Article 760</li> </ul>	• UL 13	• UL 444		
	NEC Article 770	• UL 1424			
RoHS Compliance	<ul> <li>RoHS Compliant</li> </ul>				
Appearance	<ul> <li>Opaque</li> </ul>				
Forms	Pellets				

ASTM & ISO Properties 1				
Physical	Nominal Value	Unit	Test Method	
Specific Gravity	1.34		ASTM D792	
Mechanical	Nominal Value	Unit	Test Method	
Tensile Strength (Break)	3530	psi	ASTM D638	
Tensile Elongation (Break)	300	%	ASTM D638	
Hardness	Nominal Value	Unit	Test Method	
Durometer Hardness (Shore C, 10 sec)	84		ASTM D2240	
Thermal	Nominal Value	Unit	Test Method	
Continuous Use Temperature	167	°F	ASTM D794	
Brittleness Temperature	-0.400	°F	ASTM D746	
Flammability	Nominal Value	Unit	Test Method	
Oxygen Index	31	%	ASTM D2863	

## **Notes**

## Teknor Apex Company Corporate Headquarters

In U.S. for Vinyls, TPEs, Colorants, Engineered Thermoplastics (Chem Polymer) 505 Central Avenue

Pawtucket, Rhode Island 02861 U.S.

Phone: 401-725-8000 Fax: 401-725-8095

Toll Free (U.S. only) 800-556-3864

info@teknorapex.com

Teknor Apex U.K. Ltd.

Tat Bank Road

Oldbury, West Midlands B69 4NH England

Phone: (44) 121-665-2100 Fax: (44) 121-544-5530

etpsales@teknorapex.co.uk



Revision Date: 12/12/2013

<sup>&</sup>lt;sup>1</sup> Typical properties: these are not to be construed as specifications.