

APEX® 80131

Teknor Apex Company - Flexible Polyvinyl Chloride

Friday, June 30, 2017

| | General Information | | | | |
|-----------------|---|--|-------------------------------|--|--|
| General | | | | | |
| Material Status | Commercial: Active | | | | |
| Availability | Africa & Middle EastAsia Pacific | EuropeLatin America | North America | | |
| Features | Sunlight Resistant (300 hours) | Sunlight Resistant (720 hours) | | | |
| Uses | Flexible Cord Insulation | Flexible Cord Jacketing | Transportation Wire Jacketing | | |
| Wire Types | • SJTW • SPT-1 • SPT-2 | • SPT-3 • SRDT • STW | • SVT | | |
| Agency Ratings | • UL QMTT2 | | | | |
| RoHS Compliance | RoHS Compliant | | | | |
| Appearance | Opaque | | | | |
| Forms | Pellets | | | | |

| ASTM & ISO Properties ¹ | | | | |
|--------------------------------------|---------------|---------|-------------|--|
| Physical | Nominal Value | Unit | Test Method | |
| Specific Gravity | 1.31 | | ASTM D792 | |
| Mechanical | Nominal Value | Unit | Test Method | |
| Tensile Strength (Break) | 2350 | psi | ASTM D638 | |
| Tensile Elongation (Break) | 400 | % | ASTM D638 | |
| Hardness | Nominal Value | Unit | Test Method | |
| Durometer Hardness (Shore A, 15 sec) | 80 | | ASTM D2240 | |
| Thermal | Nominal Value | Unit | Test Method | |
| Continuous Use Temperature | 221 | °F | ASTM D794 | |
| Brittleness Temperature | -38.2 | °F | ASTM D746 | |
| Electrical | Nominal Value | Unit | Test Method | |
| Volume Resistivity | 2.7E+13 | ohms·cm | ASTM D257 | |
| Dielectric Strength | 850 | V/mil | ASTM D149 | |
| Flammability | Nominal Value | Unit | Test Method | |
| Oxygen Index | 22 | % | ASTM D2863 | |

Notes

Teknor Apex Company Corporate Headquarters

In U.S. for Vinyls, TPEs, Colorants, Engineered Thermoplastics (Chem Polymer) 505 Central Avenue

Pawtucket, Rhode Island 02861 U.S.

Phone: 401-725-8000 Fax: 401-725-8095

Toll Free (U.S. only) 800-556-3864

info@teknorapex.com

Teknor Apex U.K. Ltd.

Tat Bank Road Oldbury, West Midlands B69 4NH England

Phone: (44) 121-665-2100 Fax: (44) 121-544-5530

etpsales@teknorapex.co.uk



Revision Date: 12/12/2013

¹ Typical properties: these are not to be construed as specifications.