

## **APEX® 80842**

## Teknor Apex Company - Flexible Polyvinyl Chloride

Friday, June 30, 2017

General Information					
General					
Material Status	Commercial: Active				
Availability	<ul><li> Africa &amp; Middle East</li><li> Asia Pacific</li></ul>	<ul><li>Europe</li><li>Latin America</li></ul>	North America		
Features	High Heat Resistance	<ul> <li>Sunlight Resistant (720 hours</li> </ul>	S)		
Uses	<ul> <li>Outdoor Applications</li> </ul>	<ul> <li>Wire &amp; Cable Applications</li> </ul>	Wire Jacketing		
Agency Ratings	• UL QMTT2				
RoHS Compliance	<ul> <li>RoHS Compliant</li> </ul>				
Appearance	<ul> <li>Opaque</li> </ul>				
Forms	Pellets				

ASTM & ISO Properties 1				
Physical	Nominal Value	Unit	Test Method	
Specific Gravity	1.30		ASTM D792	
Mechanical	Nominal Value	Unit	Test Method	
Tensile Strength (Break)	2400	psi	ASTM D638	
Tensile Elongation (Break)	400	%	ASTM D638	
Hardness	Nominal Value	Unit	Test Method	
Durometer Hardness (Shore A, 15 sec)	82		ASTM D2240	
Thermal	Nominal Value	Unit	Test Method	
Continuous Use Temperature	221	°F	ASTM D794	
Brittleness Temperature	-23.8	°F	ASTM D746	
Electrical	Nominal Value	Unit	Test Method	
Volume Resistivity	1.2E+14	ohms·cm	ASTM D257	
Dielectric Constant			ASTM D150	
1 kHz	5.15			
1 MHz	3.09			
Dissipation Factor			ASTM D150	
1 kHz	0.094			
1 MHz	0.079			
Flammability	Nominal Value	Unit	Test Method	
Oxygen Index	26	%	ASTM D2863	

## **Notes**

## **Teknor Apex Company** Corporate Headquarters

In U.S. for Vinyls, TPEs, Colorants, Engineered Thermoplastics (Chem Polymer) 505 Central Avenue Pawtucket, Rhode Island 02861 U.S.

Phone: 401-725-8000 Fax: 401-725-8095 Toll Free (U.S. only) 800-556-3864

Teknor Apex U.K. Ltd.

Tat Bank Road Oldbury, West Midlands B69 4NH England

Phone: (44) 121-665-2100 Fax: (44) 121-544-5530

etpsales@teknorapex.co.uk

上海松節運化科技有限公司 上海松節運化科技有限公開商 TEKNOR APEX 特诺尔爱佩斯 021-58958519 Teknorapex.shshsi.com 联系电话: 021-58958519

info@teknorapex.com

Revision Date: 12/3/2015

<sup>&</sup>lt;sup>1</sup> Typical properties: these are not to be construed as specifications.