

APEX® 80862

Teknor Apex Company - Semi-Rigid Polyvinyl Chloride

Friday, June 30, 2017

General Information					
General					
Material Status	Commercial: Active				
Availability	 Africa & Middle East Asia Pacific	EuropeLatin America	North America		
Features	High Heat Resistance	Semi Rigid			
Uses	 Cable Jacketing 	 Insulation 			
Agency Ratings	• UL 1061	• UL 1424			
RoHS Compliance	 RoHS Compliant 				
Appearance	 Opaque 				
Forms	Pellets				

ASTM & ISO Properties 1					
Physical	Nominal Value	Unit	Test Method		
Specific Gravity	1.30		ASTM D792		
Mechanical	Nominal Value	Unit	Test Method		
Tensile Strength (Break)	3450	psi	ASTM D638		
Tensile Elongation (Break)	330	%	ASTM D638		
Hardness	Nominal Value	Unit	Test Method		
Durometer Hardness (Shore C, 10 sec)	90		ASTM D2240		
Thermal	Nominal Value	Unit	Test Method		
Continuous Use Temperature	221	°F	ASTM D794		
Brittleness Temperature	-18.4	°F	ASTM D746		
Electrical	Nominal Value	Unit	Test Method		
Dielectric Constant			ASTM D150		
1 kHz	3.64				
1 MHz	2.98				
Dissipation Factor			ASTM D150		
1 kHz	0.059				
1 MHz	0.031				
Flammability	Nominal Value	Unit	Test Method		
Oxygen Index	30	%	ASTM D2863		

Notes

Teknor Apex Company Corporate Headquarters

In U.S. for Vinyls, TPEs, Colorants, Engineered Thermoplastics (Chem Polymer) 505 Central Avenue Pawtucket, Rhode Island 02861 U.S.

Phone: 401-725-8000 Fax: 401-725-8095 Toll Free (U.S. only) 800-556-3864

info@teknorapex.com

Teknor Apex U.K. Ltd.

Tat Bank Road Oldbury, West Midlands B69 4NH England

Phone: (44) 121-665-2100 Fax: (44) 121-544-5530

etpsales@teknorapex.co.uk



Revision Date: 4/14/2016

¹ Typical properties: these are not to be construed as specifications.