

APEX® 80873

Teknor Apex Company - Semi-Rigid Polyvinyl Chloride

Friday, June 30, 2017

General Information					
General					
Material Status	Commercial: Active				
Availability	 Africa & Middle East 	• Europe	North America		
Availability	Asia Pacific Latin America	• North America			
Features	 Semi Rigid 				
Uses	 Automotive Electronics 	 Insulation 			
	• AWM	• THHN			
Wire Types	• GPT	• THW	• TW		
	• TFFN	• THWN			
Agency Ratings	• SAE J1128	• UL 1581			
	• UL 1063	• UL 83			
RoHS Compliance	 RoHS Compliant 				
Appearance	Opaque				
Forms	• Pellets				

ASTM & ISO Properties ¹				
Physical	Nominal Value	Unit	Test Method	
Specific Gravity	1.30		ASTM D792	
Mechanical	Nominal Value	Unit	Test Method	
Tensile Strength (Break)	3550	psi	ASTM D638	
Tensile Elongation (Break)	320	%	ASTM D638	
Hardness	Nominal Value	Unit	Test Method	
Durometer Hardness (Shore C, 10 sec)	83		ASTM D2240	
Thermal	Nominal Value	Unit	Test Method	
Continuous Use Temperature	221	°F	ASTM D794	
Brittleness Temperature	8.60	°F	ASTM D746	
Electrical	Nominal Value	Unit	Test Method	
Dielectric Constant			ASTM D150	
1 kHz	3.59			
1 MHz	2.89			
Dissipation Factor			ASTM D150	
1 kHz	0.061			
1 MHz	0.035			
Flammability	Nominal Value	Unit	Test Method	
Oxygen Index	27	%	ASTM D2863	

Notes

¹ Typical properties: these are not to be construed as specifications.

上海松静理化科技有限公司 上海松静理化科技有限公開商 TEKNOR APEX 特诺尔爱佩斯 TEKNOR APEX 特诺尔爱佩斯 teknorapex.shshsi.com 联系电流: 021-58958519

Revision Date: 12/12/2013

APEX® 80873

Teknor Apex Company - Semi-Rigid Polyvinyl Chloride

Teknor Apex Company Corporate Headquarters

In U.S. for Vinyls, TPEs, Colorants, Engineered Thermoplastics (Chem Polymer) 505 Central Avenue

Pawtucket, Rhode Island 02861 U.S.

Phone: 401-725-8000 Fax: 401-725-8095

Toll Free (U.S. only) 800-556-3864

info@teknorapex.com

Teknor Apex U.K. Ltd.

Tat Bank Road
Oldbury, West Midlands B69 4NH England

Phone: (44) 121-665-2100 Fax: (44) 121-544-5530

etpsales@teknorapex.co.uk



Revision Date: 12/12/2013