

APEX® 84455

Teknor Apex Company - Flexible Polyvinyl Chloride

Friday, June 30, 2017

General Information						
General						
Material Status	Commercial: Active					
Availability	 Africa & Middle East Asia Pacific	EuropeLatin America	North America			
Features	Flame Retardant					
Uses	 Insulation 					
Wire Types	• AWM					
Agency Ratings	• UL 1063	• UL 1581	• UL 62			
RoHS Compliance	 RoHS Compliant 					
Appearance	 Opaque 					
Forms	• Pellets					

ASTM & ISO Properties ¹					
Physical	Nominal Value	Unit	Test Method		
Specific Gravity	1.37		ASTM D792		
Mechanical	Nominal Value	Unit	Test Method		
Tensile Strength (Break)	2900	psi	ASTM D638		
Tensile Elongation (Break)	340	%	ASTM D638		
Hardness	Nominal Value	Unit	Test Method		
Durometer Hardness (Shore C, 10 sec)	65		ASTM D2240		
Thermal	Nominal Value	Unit	Test Method		
Continuous Use Temperature	221	°F	ASTM D794		
Brittleness Temperature	-7.60	°F	ASTM D746		
Electrical	Nominal Value	Unit	Test Method		
Volume Resistivity	2.7E+13	ohms·cm	ASTM D257		
Flammability	Nominal Value	Unit	Test Method		
Oxygen Index	28	%	ASTM D2863		

Notes

Teknor Apex Company Corporate Headquarters

In U.S. for Vinyls, TPEs, Colorants, Engineered Thermoplastics (Chem Polymer) 505 Central Avenue Pawtucket, Rhode Island 02861 U.S.

Phone: 401-725-8000 Fax: 401-725-8095

Toll Free (U.S. only) 800-556-3864

info@teknorapex.com

Teknor Apex U.K. Ltd.

Tat Bank Road Oldbury, West Midlands B69 4NH England

Phone: (44) 121-665-2100 Fax: (44) 121-544-5530

etpsales@teknorapex.co.uk



Revision Date: 12/12/2013

¹ Typical properties: these are not to be construed as specifications.