

APEX® 84842 Teknor Apex Company - Flexible Polyvinyl Chloride

Friday, June 30, 2017

General Information

General				
Material Status	Commercial: Active			
Availability	 Africa & Middle East Asia Pacific	 Europe Latin America	North America	
Features	High Heat Resistance	Sunlight Resistant (720 hours)		
Uses	Cable Jacketing	Outdoor Applications		
Wire Types	• CXTW • SJTW	SPT-1WSPT-2W	• STW • XTW	
Agency Ratings	• UL 62	UL QMTT2		
RoHS Compliance	 RoHS Compliant 			
Appearance	Opaque			
Forms	Pellets			

ASTM & ISO Properties ¹					
Physical	Nominal Value	Unit	Test Method		
Specific Gravity	1.33		ASTM D792		
Mechanical	Nominal Value	Unit	Test Method		
Tensile Strength (Break)	2600	psi	ASTM D638		
Tensile Elongation (Break)	360	%	ASTM D638		
Hardness	Nominal Value	Unit	Test Method		
Durometer Hardness (Shore A, 15 sec)	86		ASTM D2240		
Thermal	Nominal Value	Unit	Test Method		
Continuous Use Temperature	221	°F	ASTM D794		
Brittleness Temperature	-22.0	°F	ASTM D746		
Electrical	Nominal Value	Unit	Test Method		
Volume Resistivity	1.6E+13	ohms∙cm	ASTM D257		
Dielectric Constant			ASTM D150		
1 kHz	4.90				
1 MHz	3.06				
Dissipation Factor			ASTM D150		
1 kHz	0.096				
1 MHz	0.075				
Flammability	Nominal Value	Unit	Test Method		
Oxygen Index	29	%	ASTM D2863		
oxygen maex	25	70	AOTIV		

Notes

上海松前塑化料技有限公司 上海松前塑化料技有限公司 基本的RAPEX特诺尔爱佩斯一级分销商 TEKNOR APEX特诺尔爱佩斯--级分销商 teknorapex.shshsi.com 联系电声: 021-58958519 ¹ Typical properties: these are not to be construed as specifications. Teknor Apex Company Teknor Apex U.K. Ltd. Corporate Headquarters Tat Bank Road In U.S. for Vinyls, TPEs, Colorants, Oldbury, West Midlands B69 4NH England Engineered Thermoplastics (Chem Polymer) 505 Central Avenue Phone: (44) 121-665-2100 Pawtucket, Rhode Island 02861 U.S. Fax: (44) 121-544-5530 Phone: 401-725-8000 Fax: 401-725-8095 etpsales@teknorapex.co.uk Toll Free (U.S. only) 800-556-3864

info@teknorapex.com

Revision Date: 12/12/2013

The information and recommendations contained in this bulletin are, to the best of our knowledge, accurate and reliable but no guarantee of their accuracy is made. All products are sold upon condition that purchasers shall make their own tests to determine the suitability of such products for their particular purposes and uses and purchasers assume all risks and liability for the results of use of the products, including use in accordance with selfer's recommendations. Nothing in this bulletin constitutes permission or a recommendation to practice or use any invention covered by any patent owned by this company or by others. There is no warranty of merchantability and there are no other warranties for the products described.