

APEX® 01-A-0402C-112

Teknor Apex Company - Semi-Rigid Polyvinyl Chloride

Friday, June 30, 2017

General Information						
General						
Material Status	Commercial: Active					
Availability	Africa & Middle EastAsia Pacific	EuropeLatin America	North America			
Uses	 Automotive Electronics 	 Insulation 				
Wire Types	• TWP					
Agency Ratings	• SAE J1128					
RoHS Compliance	 RoHS Compliant 					
Appearance	Opaque					
Forms	• Pellets					
Processing Method	Extrusion					

ASTM & ISO Properties 1					
Physical	Nominal Value	Unit	Test Method		
Specific Gravity	1.32		ASTM D792		
Mechanical	Nominal Value	Unit	Test Method		
Tensile Strength (Break)	3420	psi	ASTM D638		
Tensile Elongation (Break)	290	%	ASTM D638		
Hardness	Nominal Value	Unit	Test Method		
Durometer Hardness (Shore C, 10 sec)	88		ASTM D2240		
Thermal	Nominal Value	Unit	Test Method		
Continuous Use Temperature	221	°F	ASTM D794		
Brittleness Temperature	-16.6	°F	ASTM D746		
Flammability	Nominal Value	Unit	Test Method		
Oxygen Index	26	%	ASTM D2863		

Notes

Teknor Apex Company Corporate Headquarters

In U.S. for Vinyls, TPEs, Colorants, Engineered Thermoplastics (Chem Polymer) 505 Central Avenue

Pawtucket, Rhode Island 02861 U.S.

Phone: 401-725-8000 Fax: 401-725-8095 Toll Free (U.S. only) 800-556-3864

info@teknorapex.com

Teknor Apex U.K. Ltd.

Tat Bank Road Oldbury, West Midlands B69 4NH England

Phone: (44) 121-665-2100 Fax: (44) 121-544-5530

etpsales@teknorapex.co.uk



Revision Date: 12/12/2013

¹ Typical properties: these are not to be construed as specifications.