

Teknor Apex Company - Flexible Polyvinyl Chloride

Friday, June 30, 2017

General Information					
General					
Material Status	 Commercial: Active 				
Availability	 Africa & Middle East Asia Pacific	EuropeLatin America	North America		
Features	Flame Retardant	Sunlight Resistant (720 hou	ırs) • UV Resistant		
Uses	 Building Wire Jacketing 				
Wire Types	• SEC	• UF			
Agency Ratings	• UL QMTT2				
RoHS Compliance	 RoHS Compliant 				
Appearance	• Opaque				
Forms	• Pellets				

ASTM & ISO Properties ¹					
Physical	Nominal Value	Unit	Test Method		
Specific Gravity	1.37		ASTM D792		
Mechanical	Nominal Value	Unit	Test Method		
Tensile Strength (Break)	2560	psi	ASTM D638		
Tensile Elongation (Break)	250	%	ASTM D638		
Hardness	Nominal Value	Unit	Test Method		
Durometer Hardness (Shore C, 10 sec)	67		ASTM D2240		
Thermal	Nominal Value	Unit	Test Method		
Continuous Use Temperature	194	°F	ASTM D794		
Brittleness Temperature	-11.2	°F	ASTM D746		
Flammability	Nominal Value	Unit	Test Method		
Oxygen Index	29	%	ASTM D2863		

Notes

Teknor Apex Company Corporate Headquarters

In U.S. for Vinyls, TPEs, Colorants, Engineered Thermoplastics (Chem Polymer) 505 Central Avenue

Pawtucket, Rhode Island 02861 U.S.

Phone: 401-725-8000 Fax: 401-725-8095

Toll Free (U.S. only) 800-556-3864

info@teknorapex.com

Teknor Apex U.K. Ltd.

Tat Bank Road Oldbury, West Midlands B69 4NH England

Phone: (44) 121-665-2100 Fax: (44) 121-544-5530

etpsales@teknorapex.co.uk



Revision Date: 12/12/2013

¹ Typical properties: these are not to be construed as specifications.