

## APEX® 80118-Y

## Teknor Apex Company - Flexible Polyvinyl Chloride

Friday, June 30, 2017

General Information					
General					
Material Status	Commercial: Active				
Availability	<ul><li>Africa &amp; Middle East</li><li>Asia Pacific</li></ul>	<ul><li>Europe</li><li>Latin America</li></ul>	North America		
Features	<ul> <li>UV Resistant</li> </ul>				
Uses	Cable Jacketing	<ul> <li>Insulation</li> </ul>			
Wire Types	• TW				
Agency Ratings	<ul><li>UL 1063</li><li>UL 1581</li></ul>	• UL 62 • UL 83			
RoHS Compliance	<ul> <li>RoHS Compliant</li> </ul>				
Appearance	<ul> <li>Opaque</li> </ul>				
Forms	• Pellets				

ASTM & ISO Properties 1					
Physical	Nominal Value	Unit	Test Method		
Specific Gravity	1.39		ASTM D792		
Mechanical	Nominal Value	Unit	Test Method		
Tensile Strength (Break)	2550	psi	ASTM D638		
Tensile Elongation (Break)	280	%	ASTM D638		
Hardness	Nominal Value	Unit	Test Method		
Durometer Hardness (Shore A, 15 sec)	86		ASTM D2240		
Thermal	Nominal Value	Unit	Test Method		
Continuous Use Temperature	140	°F	ASTM D794		
Brittleness Temperature	-18.4	°F	ASTM D746		
Electrical	Nominal Value	Unit	Test Method		
Dielectric Constant			ASTM D150		
1 kHz	5.39				
1 MHz	3.46				
Dissipation Factor			ASTM D150		
1 kHz	0.089				
1 MHz	0.079				
Flammability	Nominal Value	Unit	Test Method		
Oxygen Index	23	%	ASTM D2863		

## Notes

Teknor Apex Company Corporate Headquarters

In U.S. for Vinyls, TPEs, Colorants, Engineered Thermoplastics (Chem Polymer) 505 Central Avenue Pawtucket, Rhode Island 02861 U.S.

Phone: 401-725-8000 Fax: 401-725-8095 Toll Free (U.S. only) 800-556-3864 Teknor Apex U.K. Ltd.

Tat Bank Road Oldbury, West Midlands B69 4NH England

Phone: (44) 121-665-2100 Fax: (44) 121-544-5530

etpsales@teknorapex.co.uk

info@teknorapex.com



Revision Date: 12/12/2013

<sup>&</sup>lt;sup>1</sup> Typical properties: these are not to be construed as specifications.