😰 TEKNOR APEX

APEX[®] 97-G0029C-82

Teknor Apex Company - Flexible Polyvinyl Chloride

Friday, June 30, 2017

General Information

| General | | | | |
|-------------------|---|--|---------------|--|
| Material Status | Commercial: Active | | | |
| Availability | Africa & Middle East Asia Pacific | EuropeLatin America | North America | |
| Features | Flame Retardant | | | |
| Uses | Cable Jacketing | Communication Wire Jacketing | | |
| Agency Ratings | • UL 444 | • UL 62 | | |
| RoHS Compliance | RoHS Compliant | | | |
| Appearance | Opaque | | | |
| Forms | Pellets | | | |
| Processing Method | Extrusion | | | |

| ASTM & ISO Properties ¹ | | | | |
|--------------------------------------|---------------|------|-------------|--|
| Physical | Nominal Value | Unit | Test Method | |
| Specific Gravity | 1.37 | | ASTM D792 | |
| Mechanical | Nominal Value | Unit | Test Method | |
| Tensile Strength (Break) | 2600 | psi | ASTM D638 | |
| Tensile Elongation (Break) | 300 | % | ASTM D638 | |
| Hardness | Nominal Value | Unit | Test Method | |
| Durometer Hardness (Shore A, 15 sec) | 82 | | ASTM D2240 | |
| Thermal | Nominal Value | Unit | Test Method | |
| Continuous Use Temperature | 167 | °F | ASTM D794 | |
| Brittleness Temperature | -16.6 | °F | ASTM D746 | |
| Flammability | Nominal Value | Unit | Test Method | |
| Oxygen Index | 30 | % | ASTM D2863 | |

Notes

¹ Typical properties: these are not to be construed as specifications.

Teknor Apex Company Corporate Headquarters

Teknor Apex U.K. Ltd.

In U.S. for Vinyls, TPEs, Colorants, Engineered Thermoplastics (Chem Polymer) 505 Central Avenue Pawtucket, Rhode Island 02861 U.S.

Phone: 401-725-8000 Fax: 401-725-8095 Toll Free (U.S. only) 800-556-3864

info@teknorapex.com

Tat Bank Road Oldbury, West Midlands B69 4NH England

Phone: (44) 121-665-2100 Fax: (44) 121-544-5530

etpsales@teknorapex.co.uk



Revision Date: 12/12/2013

The information and recommendations contained in this bulletin are, to the best of our knowledge, accurate and reliable but no guarantee of their accuracy is made. All products are sold upon condition that purchasers shall make their own tests to determine the suitability of such products for their particular purposes and uses and purchasers assume all risks and liability for the results of use of the products, including use in accordance with selfer's recommendations. Nothing in this bulletin constitutes permission or a recommendation to practice or use any invention covered by any patent owned by this company or by others. There is no warranty of merchantability and there are no other warranties for the products described.