TEKNOR APEX

Flexalloy[®] 89501-83FR

Teknor Apex Company - Polyvinyl Chloride Elastomer

Friday, June 30, 2017

General Information					
Seneral					
Material Status	Commercial: Active				
Availability	 Africa & Middle East Asia Pacific	EuropeLatin America	North America		
Features	High Heat Resistance	Low Temperature Flexibility			
Uses	 Wet Rated Insulation 	ation			
Wire Types	 NISPE-1 NISPE-2 SE SEO SEOW SEW SJE SJEO 	 SJEOW SJEW SPE-1 SPE-2 SPE-3 SRDE SVE SVE SVEO 	• TF • TFF • THHW • THW • TW • VW-1		
Agency Ratings	UL Class 11UL Class 12	UL Class 36UL Class 43	• UL QMTT2		
RoHS Compliance	 RoHS Compliant 				
Appearance	Opaque				
Forms	Pellets				

ASTM & ISO Properties ¹				
Physical	Nominal Value	Unit	Test Method	
Specific Gravity	1.31		ASTM D792	
Mechanical	Nominal Value	Unit	Test Method	
Tensile Strength (Break)	2600	psi	ASTM D638	
Tensile Elongation (Break)	250	%	ASTM D638	
Hardness	Nominal Value	Unit	Test Method	
Durometer Hardness (Shore A, 15 sec)	84		ASTM D2240	
Thermal	Nominal Value	Unit	Test Method	
Continuous Use Temperature	221	°F	ASTM D794	
Brittleness Temperature	-49.0	°F	ASTM D746	
Electrical	Nominal Value	Unit	Test Method	
Volume Resistivity	3.2E+13	ohms∙cm	ASTM D257	
Dielectric Strength	580	V/mil	ASTM D149	
Dielectric Constant			ASTM D150	
1 kHz	5.10			
1 MHz	3.38			
Dissipation Factor			ASTM D150	
1 kHz	0.056		公司	
1 MHz	0.089	11日1月	い時間	
Flammability	Nominal Value	Unit	589585Test Method	
Oxygen Index	0.056 0.089 Nominal Value 29 TEKNOR APEX TEKNOR APEX teknorapex.shshsi.co	加联系电话: 021	ASTM D2863	
Notes	KNOR Ar shshsj.co			
¹ Typical properties: these are not to be construed as specifications.	TER. teknorapex.			

The information and recommendations contained in this bulletin are, to the best of our knowledge, accurate and reliable but no guarantee of their accuracy is made. All products are sold upon condition that purchasers shall make their own tests to determine the suitability of such products for their particular purposes and uses and purchasers assume all risks and liability for the results of use of the products, including use in accordance with seller's recommendations. Nothing in this bulletin constitutes permission or a recommendation to practice or use any invention covered by any patent owned by this company or by others. There is no warranty of merchantability and there are no other warranties for the products described.

Flexalloy® 89501-83FR Teknor Apex Company - Polyvinyl Chloride Elastomer

Teknor Apex Company Corporate Headquarters

In U.S. for Vinyls, TPEs, Colorants, Engineered Thermoplastics (Chem Polymer) 505 Central Avenue Pawtucket, Rhode Island 02861 U.S.

Phone: 401-725-8000 Fax: 401-725-8095 Toll Free (U.S. only) 800-556-3864

info@teknorapex.com

Teknor Apex U.K. Ltd.

Tat Bank Road Oldbury, West Midlands B69 4NH England

Phone: (44) 121-665-2100 Fax: (44) 121-544-5530

etpsales@teknorapex.co.uk



Revision Date: 12/12/2013

The information and recommendations contained in this bulletin are, to the best of our knowledge, accurate and reliable but no guarantee of their accuracy is made. All products are sold upon condition that purchasers shall make their own tests to determine the suitability of such products for their particular purposes and uses and purchasers assume all risks and liability for the results of use of the products, including use in accordance with seller's recommendations. Nothing in this bulletin constitutes permission or a recommendation to practice or use any invention covered by any patent owned by this company or by others. There is no warranty of merchantability and there are no other warranties for the products described.