

- Flexible Polyvinyl Chloride

Thursday, June 29, 2017

General Information			
General			
Material Status	Commercial: Active		
Availability	Asia Pacific		
Features	Food Contact Acceptable Non-Toxic		
Uses	Hose Tubing		
Forms	• Pellets		
Processing Method	Extrusion		

ASTM & ISO Properties ¹				
Physical	Nominal Value	Unit	Test Method	
Specific Gravity	1.21		ASTM D792	
Mechanical	Nominal Value	Unit	Test Method	
Tensile Strength ² (Yield)	2130	psi	ASTM D638	
Tensile Elongation ² (Break)	320	%	ASTM D638	
Hardness	Nominal Value	Unit	Test Method	
Durometer Hardness (Shore A)	68		ASTM D2240	
Thermal	Nominal Value	Unit	Test Method	
Thermal Stability ³ (374°F)	> 50	min	BS 2782	

Notes

Teknor Apex Company Corporate Headquarters

In U.S. for Vinyls, TPEs, Colorants, Engineered Thermoplastics (Chem Polymer) 505 Central Avenue

Pawtucket, Rhode Island 02861 U.S.

Phone: 401-725-8000 Fax: 401-725-8095

Toll Free (U.S. only) 800-556-3864

Teknor Apex U.K. Ltd.

Tat Bank Road

Oldbury, West Midlands B69 4NH England

Phone: (44) 121-665-2100 Fax: (44) 121-544-5530

etpsales@teknorapex.co.uk

info@teknorapex.com



Revision Date: 1/1/2013

¹ Typical properties: these are not to be construed as specifications.

² 9.8 in/min

³ Congo Red