

500

- Flexible Polyvinyl Chloride

Thursday, June 29, 2017

General Information				
General				
Material Status	Commercial: Active			
Availability	Asia Pacific			
Uses	 Footwear 	General Purpose		
Forms	• Pellets			
Processing Method	Injection Molding			

ASTM & ISO Properties ¹					
Physical	Nominal Value	Unit	Test Method		
Specific Gravity	1.24		ASTM D792		
Mechanical	Nominal Value	Unit	Test Method		
Tensile Strength ² (Yield)	1780	psi	ASTM D638		
Tensile Elongation ² (Break)	380	%	ASTM D638		
Hardness	Nominal Value	Unit	Test Method		
Durometer Hardness (Shore A)	62		ASTM D2240		
Thermal	Nominal Value	Unit	Test Method		
Thermal Stability ³ (374°F)	> 50	min	BS 2782		

Notes

¹ Typical properties: these are not to be construed as specifications.

Teknor Apex Company Corporate Headquarters

In U.S. for Vinyls, TPEs, Colorants, Engineered Thermoplastics (Chem Polymer) 505 Central Avenue

Pawtucket, Rhode Island 02861 U.S.

Phone: 401-725-8000 Fax: 401-725-8095

Toll Free (U.S. only) 800-556-3864

Teknor Apex U.K. Ltd.

Tat Bank Road

Oldbury, West Midlands B69 4NH England

Phone: (44) 121-665-2100 Fax: (44) 121-544-5530

etpsales@teknorapex.co.uk

info@teknorapex.com



Revision Date: 10/7/2014

² 9.8 in/min

³ Congo Red