

006

- Flexible Polyvinyl Chloride

Thursday, June 29, 2017

General Information					
General					
Material Status	Commercial: Active				
Availability	Asia Pacific				
Features	Good Flexibility				
Uses	Cable Jacketing	Wire & Cable Applications			
Wire Types	• ST4 • ST5	Type 6YM1	• YM2		
Agency Ratings	• BS 6747	• IEC 60227	• VDE 0207		
Forms	Pellets				
Processing Method	Extrusion				

ASTM & ISO Properties ¹					
Physical	Nominal Value	Unit	Test Method		
Specific Gravity	1.47		ASTM D792		
Mechanical	Nominal Value	Unit	Test Method		
Tensile Strength	2470	psi	IEC 811-1-1		
Tensile Elongation ² (Break)	300	%	IEC 811-1-1		
Hardness	Nominal Value	Unit	Test Method		
Durometer Hardness (Shore A)	79		ASTM D2240		
Thermal	Nominal Value	Unit	Test Method		
Thermal Stability ³ (374°F)	> 1	hr	BS 2782		
Aging	Nominal Value	Unit	Test Method		
Change in Tensile Strength (176°F, 168 hr)	10	%	IEC 811-1-2		
Change in Ultimate Elongation (176°F, 168 hr)	20	%	IEC 811-1-2		
Electrical	Nominal Value	Unit	Test Method		
Volume Resistivity (68°F)	1.0E+14	ohms∙cm	BS 2782		

Notes

¹ Typical properties: these are not to be construed as specifications.

² 9.8 in/min

³ Congo Red

Teknor Apex Company Corporate Headquarters

505 Central Avenue

Phone: 401-725-8000 Fax: 401-725-8095

info@teknorapex.com

In U.S. for Vinyls, TPEs, Colorants,

Pawtucket, Rhode Island 02861 U.S.

Toll Free (U.S. only) 800-556-3864

Engineered Thermoplastics (Chem Polymer)

Teknor Apex U.K. Ltd.

Tat Bank Road Oldbury, West Midlands B69 4NH England

Phone: (44) 121-665-2100 Fax: (44) 121-544-5530

etpsales@teknorapex.co.uk



Revision Date: 10/9/2014

The information and recommendations contained in this bulletin are, to the best of our knowledge, accurate and reliable but no guarantee of their accuracy is made. All products are sold upon condition that purchasers shall make their own tests to determine the suitability of such products for their particular purposes and uses and purchasers assume all risks and liability for the results of use of the products, including use in accordance with seller's recommendations. Nothing in this bulletin constitutes permission or a recommendation to practice or use any invention covered by any patent owned by this company or by others. There is no warranty of merchantability and there are no other warranties for the products described.