# 29

## - Flexible Polyvinyl Chloride

Thursday, June 29, 2017

General Information			
General			
Material Status	Commercial: Active		
Availability	Asia Pacific		
Features	High Strength		
Uses	Electrical/Electronic Applications		
Forms	• Pellets		
Processing Method	Injection Molding		

ASTM & ISO Properties <sup>1</sup>				
Physical	Nominal Value	Unit	Test Method	
Specific Gravity	1.33		ASTM D792	
Mechanical	Nominal Value	Unit	Test Method	
Tensile Strength	2180	psi	IEC 811-1-1	
Tensile Elongation <sup>2</sup> (Break)	220	%	IEC 811-1-1	
Hardness	Nominal Value	Unit	Test Method	
Durometer Hardness (Shore A)	82		ASTM D2240	
Aging	Nominal Value	Unit	Test Method	
Change in Tensile Strength (212°F, 168 hr)	10	%	IEC 811-1-2	
Change in Ultimate Elongation (212°F, 168 hr)	20	%	IEC 811-1-2	
Electrical	Nominal Value	Unit	Test Method	
Volume Resistivity (68°F)	5.0E+13	ohms·cm	BS 2782	

#### Notes

#### Teknor Apex Company Corporate Headquarters

In U.S. for Vinyls, TPEs, Colorants, Engineered Thermoplastics (Chem Polymer)

505 Central Avenue

Pawtucket, Rhode Island 02861 U.S.

Phone: 401-725-8000 Fax: 401-725-8095

Toll Free (U.S. only) 800-556-3864

### Teknor Apex U.K. Ltd.

Tat Bank Road

Oldbury, West Midlands B69 4NH England

Phone: (44) 121-665-2100 Fax: (44) 121-544-5530

etpsales@teknorapex.co.uk

info@teknorapex.com



Revision Date: 10/9/2014

<sup>&</sup>lt;sup>1</sup> Typical properties: these are not to be construed as specifications.

<sup>&</sup>lt;sup>2</sup> 9.8 in/min