

- Low Density Polyethylene

Friday, June 30, 2017

General Information				
General				
Material Status	Commercial: Active			
Availability	 Africa & Middle East 	Asia Pacific	Latin America	
Additive	 Flame Retardant 			
Features	 Flame Retardant 			
Uses	• Film	Thin-walled Parts		
Appearance	Natural Color			
Forms	Pellets			

ASTM & ISO Properties 1				
Physical	Nominal Value Unit	Test Method		
Specific Gravity	1.50	ASTM D792		
Melt Mass-Flow Rate (MFR) (190°C/2.16 kg)	60 g/10 min	ASTM D1238		
Flammability	Nominal Value Unit	Test Method		
Flame Rating	VTM-2	UL 94		
Additional Information				

Suitable for use in PE Recommended Dosage: 10%

Notes

Teknor Apex Company Corporate Headquarters

In U.S. for Vinyls, TPEs, Colorants, Engineered Thermoplastics (Chem Polymer)

505 Central Avenue Pawtucket, Rhode Island 02861 U.S.

Fax: 401-725-8095 Toll Free (U.S. only) 800-556-3864

Phone: 401-725-8000

Teknor Apex U.K. Ltd.

Tat Bank Road Oldbury, West Midlands B69 4NH England

Phone: (44) 121-665-2100 Fax: (44) 121-544-5530

etpsales@teknorapex.co.uk

info@teknorapex.com



Revision Date: 12/12/2013

¹ Typical properties: these are not to be construed as specifications.