

40

- Polypropylene Copolymer

Friday, June 30, 2017

| General Information | | | |
|------------------------|----------------------------|--|--|
| General | | | |
| Material Status | Commercial: Active | | |
| Availability | Asia Pacific | | |
| Filler / Reinforcement | Talc, 40% Filler by Weight | | |
| Forms | Pellets | | |
| Processing Method | Injection Molding | | |

 ...

-

| ASTM & ISO Properties ¹ | | | |
|--|------------------|----------|-------------------------|
| Physical | Nominal Value | Unit | Test Method |
| Specific Gravity | 1.21 | | ASTM D792 |
| Melt Mass-Flow Rate (MFR) (230°C/2.16 kg) | 9.0 | g/10 min | ASTM D1238 |
| Molding Shrinkage - Flow | 7.0E-3 to 9.0E-3 | in/in | ASTM D955 |
| Mechanical | Nominal Value | Unit | Test Method |
| Tensile Strength (Yield) | 4060 | psi | ASTM D638 |
| Tensile Elongation (Break) | 20 | % | ASTM D638 |
| Flexural Modulus | 363000 | psi | ASTM D790 |
| Flexural Strength | 5080 | psi | ASTM D790 |
| Impact | Nominal Value | Unit | Test Method |
| Notched Izod Impact | 0.67 | ft·lb/in | ASTM D256 |
| Thermal | Nominal Value | Unit | Test Method |
| Deflection Temperature Under Load (66 psi, Unannealed) | 268 | °F | ASTM D648 |
| Vicat Softening Temperature | 307 | °F | ASTM D1525 ² |

Notes

¹ Typical properties: these are not to be construed as specifications.

² Loading 1 (10 N)

Teknor Apex Company Corporate Headquarters

Teknor Apex U.K. Ltd.

Tat Bank Road Oldbury, West Midlands B69 4NH England

In U.S. for Vinyls, TPEs, Colorants, Engineered Thermoplastics (Chem Polymer) 505 Central Avenue Pawtucket, Rhode Island 02861 U.S.

Phone: 401-725-8000 Fax: 401-725-8095 Toll Free (U.S. only) 800-556-3864

info@teknorapex.com

Phone: (44) 121-665-2100 Fax: (44) 121-544-5530

etpsales@teknorapex.co.uk



Revision Date: 9/26/2011

The information and recommendations contained in this bulletin are, to the best of our knowledge, accurate and reliable but no guarantee of their accuracy is made. All products are sold upon condition that purchasers shall make their own tests to determine the suitability of such products for their particular purposes and uses and purchasers assume all risks and liability for the results of use of the products, including use in accordance with seller's recommendations. Nothing in this bulletin constitutes permission or a recommendation to practice or use any invention covered by any patent owned by this company or by others. There is no warranty of merchantability and there are no other warranties for the products described.